





### Only 4.9 L Compact Design

Ultra-small footprint that saves desk space.



### Meets Energy Star 9.0 Standard

Designed for next-generation energy efficiency.



#### Supports 4 × DDR5 Memory

Delivers high bandwidth for multitasking and creative workloads.



## Quiet Operation (No PSU Fan)

External power adapter keeps noise levels ultra-low.



#### **VESA Mount Ready**

Easily mounted behind a monitor or under a desk for flexible installation.



#### **Mini Al Workstation**

Ideal for Al-enhanced productivity and edge computing tasks.



## DeskSlim B760

# DeskSlim X600

| Dimension       | 95 x 235 x 220 mm (4.9L)   | 95 x 235 x 220 mm (4.9L)  |
|-----------------|--|---|
| Power Adapter   | 240W/19V (Optional: 330W)  | 240W/19V (Optional: 330W)   |
| Video Output    | ·  | HD Audio Jacks: Line in / Front Speaker / Microphone                          |
|                 | HD Audio Jacks: Line in / Front Speaker / Microphone                 | 1 x RJ-45 LAN Port (2.5G)   |
|                 | 1 x 2.5G LAN Port  | 2 x USB 3.2 Gen1 Type-A   |
|                 | 2 x USB 3.2 Gen1 Type-A  | 2 x USB 2.0   |
|                 | 2 x USB 2.0  | 1 x USB4  |
|                 | 2 x O3B 2.0<br>Rear I/O :  | Rear I/O:   |
|                 | 2 x USB 3.2 Gen1 Type-A<br>2 x USB 2.0                               | 2 x USB 3.2 Gen1 Type-A<br>2 x USB 2.0  |
|                 | 1 x USB 3.2 Gen1 Type-C  | 1 x USB 3.2 Gen1 Type-C   |
|                 | 1 x Headphone/Headset Jack   | 1 x Headphone/Headset Jack  |
|                 | Front I/O:   | Front I/O:  |
|                 |  | <u> </u>  |
|                 | 1 x HDMI (4K@60Hz)   | 1 x DisplayPort 1.4 (4K@120Hz)<br>1 x HDMI (4K@120Hz)                         |
|                 | 2 x DisplayPort (8K@60Hz)  | 1 x USB4  |
|                 |  | 1LICD4  |
| Expansion Slots | 1 x M.2 2230 slot for Wi-Fi/BT module and Intel® CNVi                | 1 x M.2 2230 slot for Wi-Fi/BT module   |
|                 | 1 x PCle 5.0 x 16 slot   | 1 x PCle 5.0 x 16 slot  |
| Storage         | 1 x M.2 2280 Slot for PCIe Gen4x4 SSD                                | 1 x M.2 2280 Slot for PCIe Gen4x4 SSD   |
|                 | 1 x M.2 2280 Slot for SATA/PCIe Gen4x4 SSD                           | 1 x M.2 2280 Slot for PCIe Gen5x4 SSD   |
|                 | 2 x SATA 6Gb/s Ports   | 2 x SATA 6Gb/s Ports  |
| Graphics        | Supports low-profile, dual-slot discrete graphics cards up to 200 mm | Supports low-profile, dual-slot discrete graphics cards up to 200 mm          |
| Memory          |  | Max. 256GB  |
|                 | Supports 4 x DDR5-5600MHz memory, Max. 256GB                         | Supports 4 x DDR5, up to 7200+(OC) ECC/non-ECC memory,                        |
| Cooler          | Supports Intel® CPU Cooler (Max. Height ≤ 71mm)                      | Supports AMD AM4/AM5 Cooler (Max. Height ≤ 71 mm)                             |
| Chipset         | Intel® B760  | AMD X600  |
| CPU             | Supports 14th/13th/12th Gen Intel® Core™ Processors, up to 125W      | Supports AMD Socket AM5 Ryzen™ 9000/8000/7000 Series<br>Processors, up to 65W |