

Fanned BOX



KEY FEATURES

- AMD Ryzen™ 4000U-Series
(4X4 BOX-4800U/4X4 BOX-4500U/4X4 BOX-4300U)
- 2 x 260-pin SO-DIMM up to 64GB DDR4 3200 MHz
- 3 x USB 3.2 Gen2, 2 x USB 2.0, 1 x M.2 Key M, 1 x M.2 Key E (WiFi-6), 1 x SATA3
- 1 x Realtek 1 Gigabit LAN (support DASH), 1 x Realtek 2.5 Gigabit LAN
- Supports Quad display, 1 x HDMI 2.0a, 3 x DP 1.2a (2 from Type C)
- TPM onboard
- 19V/90W Power Adapter
- 110.0 x 117.5 x 47.85mm, Fanned Barebone

SPECIFICATIONS

Processor System

CPU	4X4 BOX-4800U (AMD Ryzen™ 7 4800U, 8Cores, Max Speed up to 4.2GHz) 4X4 BOX-4500U (AMD Ryzen™ 5 4500U, 6Cores, Max Speed up to 4.0GHz) 4X4 BOX-4300U (AMD Ryzen™ 3 4300U, 4Cores, Max Speed up to 3.7GHz)
Chipset	SoC
BIOS	AMI SPI 128 Mbit

Memory

Technology	Dual Channel DDR4 3200 MHz
Capacity	64GB (32 GB per DIMM)
Socket	2 x 260-pin SO-DIMM

Graphics

Controller	AMD Radeon™ Graphics
HDMI	HDMI 2.0a Max resolution up to 4096x2160@60Hz
DisplayPort	DisplayPort 1.2a, DP++ Max resolution up to 4096x2160@60Hz
MultiDisplay	Max 4 display (Included 2 outputs from Type C)

Expansion Slot

M.2/WLAN	1 x Wi-Fi 6 802.11ax (2.4Gbps) + BT 5.0 (M.2 Key E, 2230 PCIe x1, USB 2.0 for Wireless)
----------	--

Audio

Interface	Realtek ALC233, High Definition Audio.
-----------	--

Ethernet

Controller/ Speed	LAN1: Realtek RTL8125BG with 10/100/1000/2500 Mbps LAN2: Realtek R8111FPV with 10/100/1000 Mbps, support DASH function
Connector	2 x RJ-45

Storage

M.2	1 x M.2 (KEY M, 2242/2260/2280) with PCIe x4 and SATA3 for SSD *M.2 Key M 2280(Supported by bracket)
SATA	1 x SATA3.0 (6.0 Gb/s)

Front I/O

USB	1 x USB 3.2 Gen2 (Type A) 2 x USB 3.2 Gen2 (Type C, Supports DP1.2a display output)
Audio	1 (headphone & microphone jack)

Rear I/O

HDMI	1 x HDMI 2.0a
DisplayPort	1 x DP1.2a
Ethernet	1 x 1 Gigabit LAN, 1 x 2.5 Gigabit LAN
USB	2 x USB 2.0
DC Jack	1

Watchdog Timer

Output	From Super I/O to drag RESETCON#
Interval	256 Segments, 0, 1, 2, ...255sec

Power Requirements

Input PWR	1 x 19V/90W Power Adapter
Power On	AT/ATX Supported - AT : Directly PWR on as power input ready - ATX : Press button to PWR on after power input ready

Environment

Operating Temp	0°C ~ 40°C
Storage Temp	-40°C ~ 85°C
Operating Humidity	5% ~ 90%
Storage Humidity	5% ~ 90%

Mechanical

Construction	Plastic
Mounting	VESA mounting
Dimensions (W x D x H)	110.0 x 117.5 x 47.85mm
Weight	Net Weight: 1kg

Others

OS Support	Windows 10
Certifications	CE, FCC Class A
Packing List	1 x 19V/90W Power Adapter 1 x Screw Package 1 x Product DVD 1 x VESA mounting bracket 1 x Bracket for M.2 2280 support