



KEY FEATURES

- Intel® Alder Lake-N Processors
- 1 x 262-pin SO-DIMM DDR5 4800 MHz, up to 32GB
- 3 x USB3.2 Gen2, 3 x USB2.0, 1 x M.2 Key E, 1 x M.2 Key M, 1 x M.2 Key B, 3 x COM, 1 x SATA3
- 2 x Intel 1 Gigabit LAN
- Supports dual display, 1 x HDMI 2.0b, 1 x DP 1.4b
- BOM Options:
 - 1*COM can be changed to additional 2*1G LAN Ports (iBOX-263J-4L)
- 1 x 19V/65W AC-DC power brick adapter
- 200 x 134.5 x 39mm (7.87" x 5.3" x 1.54"), Fanless Barebone

SPECIFICATIONS

Processor System

CPU	Intel® Alder Lake-N SoC Processors
Chipset	iBOX-263J (N97, QC, Max Speed Up to 3.6GHz, 12W)
BIOS	SoC
	AMI SPI 256 Mbit

Memory

Technology	Single Channel DDR5 4800 MHz
Capacity	32GB
Socket	1 x 262-pin SO-DIMM

Graphics

Controller	Intel® UHD Graphics
HDMI	HDMI 2.0b Max resolution up to 4096 x 2160@60Hz
DisplayPort	DP 1.4a Max resolution up to 4096 x 2160@60Hz
MultiDisplay	Dual Display

Audio

Interface	Realtek ALC256 HD, High Definition Audio
-----------	--

Ethernet

Controller/ Speed	LAN1: Intel® I210AT with 10/100/1000 Mbps LAN2: Intel® I210AT with 10/100/1000 Mbps
Connector	2 x RJ-45

Storage

M.2	1 x M.2 (Key M, 2242/2280) with PCIe Gen3 x1 and SATA3 for SSD
SATA	1 x SATA3 (6Gb/s)

Front I/O

USB	2 x USB 2.0
COM	3 x COM (RS-232) * BOM Options: 1*COM can be changed to additional 2*1G LAN Ports (iBOX-263J-4L)

Rear I/O

HDMI	1 x HDMI2.0b
DisplayPort	1 x DP 1.4a
Ethernet	2 x 1 Gigabit LAN
USB	3 x USB 3.2 Gen2, 1 x USB 2.0

Watchdog Timer

Output Interval	From Super I/O to drag RESETCON# 256 Segments, 0, 1, 2, ...255sec
-----------------	--

Power Requirements

Input PWR	9~36V DC-In
Power On	AT/ATX Supported - AT : Directly PWR on as power input ready - ATX : Press button to PWR on after power input ready

Environment

Operating Temp	-20°C ~ 50°C (With extended temp. peripherals)
Storage Temp	-40°C ~ 85°C
Operating Humidity	10% ~ 90%
Storage Humidity	10% ~ 90%

Mechanical

Construction	Aluminum housing
Mounting	VESA mount/Wall mount/Din-rail
Dimensions (L x W x H)	200 x 134.5 x 39mm (7.87" x 5.3" x 1.54")
Weight	Net Weight:1.3kg

Others

OS Support	Windows 10/11
TPM	Intel® PTT
Certifications	CE, FCC
Packing List	1 x 19V/65W Power Adapter 1 x Wall mount kit