

iEP-6020E Series

Industrial IoT Controller



Basic SKU

POE SKU

5G SKU

4POE SKU

KEY FEATURES

- NVIDIA Jetson Orin NX 16GB SOM Super Mode support, up to 157 SPARSE (78 DENSE) INT8 TOPS
- NVIDIA Jetson Orin NX 8GB SOM Super Mode support, up to 117 SPARSE (58 DENSE) INT8 TOPS
- NVIDIA Jetson Orin Nano 8GB SOM Super Mode support, up to 67 SPARSE (33 DENSE) INT8 TOPS
- NVIDIA Jetson Orin Nano 4GB SOM Super Mode support, up to 34 SPARSE (17 DENSE) INT8 TOPS
- POE SKU integrates 2x POE ports. Each port supports IEEE 802.3AF
- 4POE SKU integrates 4x POE ports. Each port supports IEEE 802.3AF
- Anti Shock and Vibration
- Wide Range Operating Temperature
- 12-36V Phoenix type DC IN support
- Wall Mount or DIN-Rail for Vertical IPC Installation (All SKU)
- Wall Mount or VESA Mount for Horizontal IPC Installation (BASIC SKU only)
- Carrier board reserved 2pcs Four Lane MIPI-CSI2 connectors (Option)*

SPECIFICATIONS

Processor System

| | |
|------------------|---|
| System on Module | <ul style="list-style-type: none"> - NVIDIA Jetson Orin NX SOM 16GB support (Basic SKU iEP-6020E-000, PoE SKU iEP-6020E-001, 4PoE SKU iEP-6020E-002, 5G SKU iEP-6020E-003) - NVIDIA Jetson Orin NX SOM 8GB support (Basic SKU iEP-6021E-000) - NVIDIA Jetson Orin Nano SOM 8GB support (Basic SKU iEP-6022E-000, PoE SKU iEP-6022E-001, 4PoE SKU iEP-6022E-002, 5G SKU iEP-6022E-003) - NVIDIA Jetson Orin Nano SOM 4GB support (Basic sku iEP-6023E-000) |
| Video | 1 x HDMI 2.0 (Orin NX)/ 1.4 (Orin Nano) |
| Memory | <ul style="list-style-type: none"> 16GB 128-bit LPDDR5 (Jetson Orin NX 16GB) 8GB 128-bit LPDDR5 (Jetson Orin NX 8GB) 8GB 128-bit LPDDR5 (Jetson Orin Nano 8GB) 4GB 64-bit LPDDR5 (Jetson Orin Nano 4GB) |
| TPM | TPM2.0 |

I/O Interface

| | |
|----------------|---|
| Ethernet | 2x 1G LAN (LAN1 from SOM, LAN2 from Intel I210AT) |
| PoE (Option) | <ul style="list-style-type: none"> 2x Intel I210AT ports, each port supports IEEE 802.3AF PoE (Orin NX SOM 16GB PoE SKU iEP-6020E-001, Orin Nano SOM 8GB PoE SKU iEP-6022E-001) 4x Intel I210IT ports, each port supports IEEE 802.3AF PoE (Orin NX SOM 16GB 4PoE SKU iEP-6020E-002, Orin Nano SOM 8GB 4PoE SKU iEP-6022E-002) |
| Serial Port | 1 x RS-232, 1 x RS-232/422/485 (Pin9 default is N/A, +5V or +12V/1A software programmable) |
| USB | 2 x USB 3.2 Gen 2x1 (one with Locking) |
| Proprietary IO | <ul style="list-style-type: none"> 2 x USB 2.0, 1 x Micro USB 2.0 (Device mode only, for OS Flash) DPR connector: 1 x DB15 for 4⁺DI, 4⁺DO, GND, Power Pin (Default is N/A, +5V/1A software programmable), PowerOn, LED+, LED-, GND, Reset ISC connector: 1 x DB15 for Power Pin(Default is N/A, +3V/1A software programmable), 5 x GND, 1 x I2C, 1 x SPI, 1 x CANBUS |

Expansion

| | |
|----------------------|--|
| SIM | 1 x Nano SIM Card slot |
| RF& Antenna (Option) | up to 4 x 5G/4G LTE antenna + 2 x Wi-Fi antenna for 5G SKU |
| M.2 Socket | <ul style="list-style-type: none"> 1 x M.2 (Key B, 3042/3052/2280) -For PCIe Gen3 x1 / USB3.2 Gen2x1 5G module (Option) (5G SKU Only, Orin NX SOM 16GB 5G SKU iEP-6020E-003, Orin Nano SOM 8GB 5G SKU iEP-6022E-003) -For PCIe Gen3 x1 / USB3.2 Gen2x1 4G LTE module (Option) (5G SKU Only, Orin NX SOM 16GB 5G SKU iEP-6020E-003, Orin Nano SOM 8GB 5G SKU iEP-6022E-003) -For PCIe Gen3 x1 M.2 B Key 2280 SSD module (Option, Basic SKU Only, Orin NX SOM 16GB Basic SKU iEP-6020E-000, Orin NX SOM 8GB Basic SKU iEP-6021E-000, Orin Nano SOM 8GB Basic SKU iEP-6022E-000, Orin Nano SOM 4GB Basic SKU iEP-6023E-000) 1 x M.2 (Key E, 2230) for PCIe Gen3 x1 Wi-Fi and USB2.0 Bluetooth module (Option) (For all SKU except 4POE SKU Orin NX SOM 16GB 4POE SKU iEP-6020E-002, Orin Nano SOM 8GB 4POE SKU iEP-6022E-002) |

Power Requirements

| | |
|---------------------------|---|
| DC Input | <ul style="list-style-type: none"> DC IN source: 12V-36V DC input, 80V Surge Protection. OVP, UVP, OCP, Reverse Protection, Phoenix type connector |
| AC to DC Adaptor (Option) | <ul style="list-style-type: none"> For Basic SKU: 120W Adapter, AC input 100-240Vac, 1.8A 50-60Hz, DC output 19V, 6.32A For POE/4POE/5G SKU: 330W Adapter, AC input 100-240Vac, 4.2A 50-60Hz, DC output 24V, 13.75A |

Storage Device

| | |
|--------------------|---|
| M.2 Socket | For Orin NX 16GB/8GB SOM Super Mode 1 x M.2(KeyM, 2280) for widetemperature PCIe Gen3 x 4 or PCIeGen4x4 SSD For Orin Nano 8GB/4GB SOM Super Mode 1 x M.2 (Key M, 2280) for wide temperature PCIe Gen3 x 4 SSD |
| Micro SD Card slot | 1 x Micro SD Card Slot (UHS-I/SDR-50) |

Mechanical

| | |
|-------------------|--|
| Dimensions | Basic SKU : 59(W) x 170(H) x 134(D) mm POE/4POE/5G SKU : 72(W) x 170(H) x 134(D) mm |
| Indicator | 1 x Storage LED |
| Function | Power on button with LED, OS Flash Button, Reset Tact Switch Enable/Disable Auto power on Switch |
| Net Weight | 1.7Kg |
| Mounting (Option) | <ul style="list-style-type: none"> Horizontal Wall mounting or - VESA mounting bracket (Basic SKU only) - Vertical Wall mounting or Din Rail mounting bracket (All SKU) |

Environmental

| | |
|-----------------------|--|
| Operating Temperature | For Orin NX 16GB/8GB SOM Super Mode Operating temperature is -25° C-50° C (w/ air flow 0.5-0.8m/s) for Basic/PoE/4PoE/5G sku(with 4G LTE or 5G module), SSD PCIe Gen3x4 or PCIe Gen4x4. For Orin Nano 8GB/4GB SOM Super Mode Operating temperature is -25° C-60° C (w/ air flow 0.5-0.8m/s) for Basic/PoE/4PoE/5G sku(with 4G LTE module), SSD PCIe Gen3x4. Operating temperature is -25° C-55° C (w/ air flow 0.5-0.8m/s) for 5G sku(with 5G module), SSD PCIe Gen3x4 |
| Storage Temperature | -40°C-85°C (-40°F-185°F) |
| Humidity | ~90% @ 45°C (non-condensing) |
| EMC | CE, FCC Class A (EN61000-6-4/-2) |
| Safety | LVD(TBD) |
| Shock | IEC 60068-2-27, Operating Shock 100G with 11 ms duration, half sine wave |
| Vibration | IEC 60068-2-64, Operating Random Vibration 5 Grms, 5-500 Hz, 3 axes, 30 min/axis |

Add-on Feature / OS Support

| | |
|-----------------------|--|
| Carrier board feature | Carrier board reserved 2pcs Four Lane MIPI-CSI2 connectors (Option)* |
| OS Support | NVIDIA JetPack 6.2 |

*MIPI-CSI2 camera need to be turned off before system going to sleep mode. It is current NVIDIA JetPack limitation.