

AMD RAID Installation Guide

1. AMD BIOS RAID Installation Guide	2
1.1 Introduction to RAID.....	2
1.2 RAID Configurations Precautions	4
1.3 Installing Windows® OS With RAID Functions	5
1.3.1 RAID Functions for AMD A85X, A75, A55, A58 chipsets	5
1.3.2 RAID Functions for AMD A88X, A78 chipsets	9
1.4 Create Disk Array.....	12
1.4.1 Configuring RAID Option ROM For AMD A85X/A75/A55/A58 Chipsets.....	12
1.4.2 Configuring Legacy RAID ROM For AMD A88X/A78 Chipset	15
2. AMD Windows RAID Installation Guide.....	18
2.1 Components of RAIDXpert Installation Software	18
2.2 Browser Support.....	18
2.3 Installing RAIDXpert	19
2.4 Logging into RAIDXpert	21
2.5 Regular Connection	22
2.6 Secure Connection	22
2.7 Creating a New Logical Drive.....	23
2.8 Connecting to RAIDXpert from the Internet	25
2.9 Running RAIDXpert without Network Connection.....	25
2.10 Using RAIDXpert2 to Create RAID Array in Windows (for AMD A88X/A78 Chipset)	27
Appendix –rcadm.efi information for AMD A88X/A78	32

1. AMD BIOS RAID Installation Guide


AMD BIOS RAID Installation Guide is an instruction for you to configure RAID functions by using the onboard FastBuild BIOS utility under BIOS environment. After you make a SATA driver diskette, press <F2> or to enter BIOS setup to set the option to RAID mode by following the detailed instruction of the “User Manual” in our support CD, then you can start to use the onboard RAID Option ROM Utility to configure RAID.

1.1 Introduction to RAID

The term “RAID” stands for “Redundant Array of Independent Disks”, which is a method combining two or more hard disk drives into one logical unit. For optimal performance, please install identical drives of the same model and capacity when creating a RAID set.

RAID 0 (Data Striping)

RAID 0 is called data striping that optimizes two identical hard disk drives to read and write data in parallel, interleaved stacks. It will improve data access and storage since it will double the data transfer rate of a single disk alone while the two hard disks perform the same work as a single drive but at a sustained data transfer rate.




WARNING!!

Although RAID 0 function can improve the access performance, it does not provide any fault tolerance. Hot-Plug any HDDs of the RAID 0 Disk will cause data damage or data loss.


RAID 1 (Data Mirroring)

RAID 1 is called data mirroring that copies and maintains an identical image of data from one drive to a second drive. It provides data protection and increases fault tolerance to the entire system since the disk array management software will direct all applications to the surviving drive as it contains a complete copy of the data in the other drive if one drive fails.




RAID 5 (Block Striping with Distributed Parity)

RAID 5 stripes data and distributes parity information across the physical drives along with the data blocks. This organization increases performance by accessing multiple physical drives simultaneously for each operation, as well as fault tolerance by providing parity data. In the event of a physical drive failure, data can be re-calculated by the RAID system based on the remaining data and the parity information. RAID 5 makes efficient use of hard drives and is the most versatile RAID Level. It works well for file, database, application and web servers.



RAID 10 (Stripe Mirroring)

RAID 0 drives can be mirrored using RAID 1 techniques, resulting in a RAID 10 solution for improved performance plus resiliency. The controller combines the performance of data striping (RAID 0) and the fault tolerance of disk mirroring (RAID 1). Data is striped across multiple drives and duplicated on another set of drives.



1.2 RAID Configurations Precautions

1. Please use two new drives if you are creating a RAID 0 (striping) array for performance. It is recommended to use two SATA drives of the same size. If you use two drives of different sizes, the smaller capacity hard disk will be the base storage size for each drive. For example, if one hard disk has an 80GB storage capacity and the other hard disk has 60GB, the maximum storage capacity for the 80GB-drive becomes 60GB, and the total storage capacity for this RAID 0 set is 120GB.
2. You may use two new drives, or use an existing drive and a new drive to create a RAID 1 (mirroring) array for data protection (the new drive must be of the same size or larger than the existing drive). If you use two drives of different sizes, the smaller capacity hard disk will be the base storage size. For example, if one hard disk has an 80GB storage capacity and the other hard disk has 60GB, the maximum storage capacity for the RAID 1 set is 60GB.
3. Please verify the status of your hard disks before you set up your new RAID array.

WARNING!!

Please backup your data first before you create RAID functions. In the process you create RAID, the system will ask if you want to "Clear Disk Data" or not. It is recommended to select "Yes", and then your future data building will operate under a clean environment.

1.3 Installing Windows® OS With RAID Functions

If you want to install Windows® 7 / 7 64-bit / 8 / 8 64-bit / 8.1 / 8.1 64-bit on a RAID disk composed of 2 or more SATA

HDDs with RAID functions, please follow below procedures according to the OS you install.

1.3.1 RAID Functions for AMD A85X, A75, A55, A58 chipsets

Way 1:

Use legacy RAID ROM to create and configure the RAID disk. The RAID disk will be created in MBR mode which the size of the RAID disk is limited to 2TB. For RAID disk size larger than 2TB, please refer to **Way 2** (UEFI Mode for GPT partition).

STEP 1: Set up UEFI

- A. During system boot, press <F2> or key to enter UEFI setup utility.
- B. Go to Advanced→ Storage Configuration.
- C. Set the "SATA Mode" option to <RAID>.
- D. Click <F10> to save to exit.

STEP 2: Create and configure the RAID disk

- A. During system boot, press <Ctrl+F> to enter legacy RAID ROM utility.
- B. Follow the instruction inside the RAID ROM utility to create the target RAID disk.
(Please refer to Section 1.4 in this guide for more details)

STEP 3: Copy RAID driver to a USB flash drive

- A. Please install the DVD-ROM into one of the SATA ports 5 ~ 8 which support IDE Combined Mode.
- B. During system boot, press <F2> or key to enter UEFI setup utility.
- C. Plug a USB drive into one of the USB port.
- D. Insert the Support CD into the DVD-ROM drive.
- E. Go to Tools→ Easy RAID Installer
- F. Follow instructions to finish the driver copy process.

STEP 4: Windows installation

- A. During Windows installation process, when Disk selection page show up, please click <Load Driver>.
- B. Click <Browse> to find the driver inside your USB flash drive.
- C. For 32bit OS, the driver is under /I386 directory. For 64bit OS, the driver is under /AMD64 directly. Please select the correct driver for your Windows version (Windows 7/8/8.1).
- D. After RAID driver is loaded, the RAID disk will show up.
- E. Please follow Windows installation instruction to finish the process.

Way 2: (for Windows® 8 64-bit / 8.1 64-bit only)


Create and configure the RAID disk in GPT mode to support RAID disk size over 2TB and speed up system boot time.

STEP 1: Set up UEFI


- A. Enter UEFI SETUP UTILITY → Advanced screen → Storage Configuration.
- B. Set the “SATA Mode” option to <RAID>.
- C. Set the “Onboard RAID 3TB+ Unlocker” option to <UEFI Mode For GPT Partition>.




- D. Click <F10> to save and exit.
- E. Click <F11> to enter boot menu and select “Built-in EFI shell”.



- F. At the **Shell>** prompt, enter the command “drvcfg” and click <Enter>.



- G. When the following screen appears, enter “dh <Drv number>” and click <Enter>.



- H. Enter “drvcfg(space)-s(space)<Drv number>(space)<Ctrl number>” and click <Enter> to access RAID Utility.

```

Configuration2 (A1D001E0)
Shell> drvcfg -s 6B 10C_

```

- I. Enter <Logical Drive Main Menu> to set up RAID Drive.

```

RAID Utility (c) 2012 Advanced Mi
+ Main Menu
+ Driver Information Menu
+ Physical Device Main Menu
+ Logical Drive Main Menu

```

- J. Choose <Logical Drive Create Menu> to create a RAID Drive.

```

RAID Utility (c) 2012 Advanced M
+ Logical Drive Main Menu
+ Logical Drive List Menu
+ Logical Drive Create Menu
+ Logical Drive Delete Menu

```

- K. Choose <Usable Physical Drive List> and select the hard drives to be included in the RAID array.

Click <Space> on keyboard to toggle checkbox. Then choose <Basic Setting>.

```

RAID Utility (c) 2012 Advanced Micro Devices, Inc. [Rev. 1.0.0.42]
+ Logical Drive Create Menu
+ Usable Physical Drive List
- Hitachi HDS723030ALA640 | 3000.59 GB [X]
- Hitachi HDS723030ALA640 | 3000.59 GB [X]
+ Basic Setting

```

- L. Enter <Ld Name>.

Choose <Ld Size setting> and set <LD Size (GB)> to LD Max Size.



Choose <Start To Create> and click <Enter> on keyboard to create logical drive.

```



AID Utility (c) 2012 Advanced Micro Devices, Inc. [Re
+ Logical Drive Create Menu
- Raid Mode : <RAID 0>
- Stripe Block (KB) : <64>
- Setcor Size (Bytes): <512>
- Initialization : <Fast>
- Gigabyte Boundary : <Disable>
- Read Policy : <Read Ahead>
- Write Policy : <Write Back>
- Ld Name : asrock
+ Ld Size Setting
- Ld Max Size : 6001.18 GB
- Ld Size (GB) : [6001]
+ Start To Create

```


- M. Click <Enter> two times.



- N. Click <Esc> to return to the previous page and choose <Logical Drive List Menu> to check the logical drive list.
Press <F10> to save and exit.




- O. Enter UEFI SETUP UTILITY → Boot to set the "Fast Boot" option to <Ultra Fast>. Press <F10> to save change and exit.



STEP 2: Windows® 8 64-bit / 8.1 64-bit OS installation

Click <F11> to enter boot menu and select "UEFI" DVD-ROM to install OS.



1.3.2 RAID Functions for AMD A88X, A78 chipsets

Way 1:

Use legacy RAID ROM to create and configure the RAID disk. The RAID disk will be created in MBR mode which the size of the RAID disk is limited to 2TB. For RAID disk size larger than 2TB, please refer to **Way 2** (UEFI Mode for GPT partition).

STEP 1: Set up UEFI

- A. During system boot, press <F2> or key to enter UEFI setup utility.
- B. Go to Advanced→ Storage Configuration.
- C. Set the "SATA Mode" option to <RAID>.
- D. Click <F10> to save to exit.

STEP 2: Create and configure the RAID disk

- A. During system boot, press <Ctrl+R> to enter legacy RAID ROM utility.
- B. Follow the instruction inside the RAID ROM utility to create the target RAID disk.
(Please refer to Section 1.4 in this guide for more details)

STEP 3: Copy RAID driver to a USB flash drive

- A. Please install the DVD-ROM into one of the SATA ports 5 ~ 8 which support IDE Combined Mode.
- B. During system boot, press <F2> or key to enter UEFI setup utility.
- C. Plug a USB drive into one of the USB port.
- D. Insert the Support CD into the DVD-ROM drive.
- E. Go to Tools→ Easy RAID Installer
- F. Follow instructions to finish the driver copy process.

STEP 4: Windows installation

- A. During Windows installation process, when Disk selection page show up, please click <Load Driver>.
- B. Click <Browse> to find the driver inside your USB flash drive.
- C. For 32bit OS, the driver is under /I386 directory. For 64bit OS, the driver is under /AMD64 directly. Please select the correct driver for your Windows version (Windows 7/8/8.1).
- D. After RAID driver is loaded, the RAID disk will show up.
- E. Please follow Windows installation instruction to finish the process.

Way 2: (for Windows® 8 64-bit / 8.1 64-bit only)

Create and configure the RAID disk in GPT mode to support RAID disk size over 2TB and speed up system boot time.


STEP 1: Set up UEFI

- A. Enter UEFI SETUP UTILITY → Advanced screen → Storage Configuration.
- B. Set the "SATA Mode" option to <RAID>.

- C. Set the "Onboard RAID 3TB+ Unlocker" option to <UEFI Mode For GPT Partition >.




- D. Click <F10> to save and exit.
- E. Click <F11> to enter boot menu and select "Built-in EFI shell".



- F. At the **Shell>** prompt, enter the command "rcadm -M -qa" and click <Enter> to show RAID information.

* Please refer to the step 3 of Section 1.3.2 to copy rcadm.efi file to USB flash disk or download the file from ASRock website [http://download.asrock.com/drivers/AMD/SATA/BoltonRAID\(v6.1.0.00117\).zip](http://download.asrock.com/drivers/AMD/SATA/BoltonRAID(v6.1.0.00117).zip).

*See the Appendix section for more information on "rcadm.efi".



G. When the following screen appears, enter “rcadm -M -id -d 0 1” and click <Enter> to initialize disk.

```
Shell> rcadm -M -id -d 0 1

initializing disk 0

initializing disk 1

Shell> _
```

H. Enter “rcadm -C <raid_type> -d <list>” and click <Enter> to create RAID disk.

RAID Types:


--volume,	-v	Single disk or concatenation of disks (JBOD)
--raidable,	-ra	Single disk, RAIDable
--raid0,	-r0	Stripe of two or more disks
--raid1,	-r1	Mirror of two disks
--raid10,	-r10	Stripe set of mirror sets
--raid5,	-r5	Stripe set with parity, three to sixteen disks

```
Shell> rcadm -C -r0 -d 0 1

created successfully


Shell> _
```

I. Enter UEFI SETUP UTILITY → Boot to set the “Fast Boot” option to <Ultra Fast>. Press <F10> to save change and exit.



STEP 2: Windows® 8 64-bit / 8.1 64-bit OS installation

Click <F11> to enter boot menu and select “UEFI” DVD-ROM to install OS.



1.4 Create Disk Array

Power on your system. If this is the first time you have booted with the disk drives installed, the AMD onboard RAID Option ROM Utility will display the following screen.

```
RAID Option ROM Version 3.0.1540.xx
(c) 2008 Advanced Micro Devices, Inc. All rights reserved.

ID      MODE      LD SIZE      TRACK MAPPING      STATUS
01      1x2 RAID 1      79.9GB      9604/255/63      Functional

Port    Device Name
3       WDC WD3600D-00FNA0
4       Maxtor 6B100S0

Press <Ctrl-F> to enter RAID Option ROM Utility...
```

The RAID Option ROM includes a Utility with tools to set up your physical drives as RAID logical drives. The RAID Option ROM Utility can perform these functions:


- Monitoring RAID status
- Viewing physical drive assignments
- Secure erasing of all data on physical drives
- Creating RAID logical drives
- Creating multiple logical drives using the same physical drives
- Deleting RAID logical drives
- Diagnosing critical and offline RAID logical drives
- Displaying the IRQ and base address (for system diagnosis)

1.4.1 Configuring RAID Option ROM For AMD A85X/A75/A55/A58 Chipsets

During the POST process, press <Ctrl+F> keys, then the RAID Option ROM Utility Main Menu appears.



Press 2 on the Main Menu screen to display the Define LD Menu. Press <Ctrl+C> to create a RAID array.



Press the arrow keys to highlight an option. Press the spacebar to cycle through logical drive types, including RAID 0, RAID 1, RAID 5 and RAID 10.




WARNING!!

While you are allowed to use any available RAID level for your bootable logical drive, it is recommended to use RAID 1 for most applications.

Press the arrow key to move to Disk Assignments. Press the spacebar to toggle between N and Y for each available drive. Y means this disk drive will be assigned to the logical drive. Assign the appropriate number of disk drives to your logical drive. Then press <Ctrl-Y> to save your logical drive configuration.



Press <Ctrl-Y> to input the LD Name.



Press Ctrl-Y to Modify Array Capacity or press any other key to use maximum capacity...

Choose one of the following actions:

1. **Use the full capacity of the disk drives for a single logical drive:** Please read "One Logical Drive" below.
2. **Split the disk drives among two logical drives:** Please read "Two Logical Drives" below.

One Logical Drive

After selecting the logical drive in Disk Assignments as the above-mentioned procedures, press any key (except for <Ctrl-Y>) to use the full portion of the logical drive for one logical drive. Then please follow the steps below:

1. Press <Esc> to exit to the Main Menu.
2. Press <Esc> again to exit the Utility.
3. Press <Y> to restart your computer.

You have successfully created a new RAID logical drive. Please install the operating system to your computer by following the detailed instruction of the "User Manual" in our support CD.

Two Logical Drives

After selecting the logical drive in Disk Assignments as the above-mentioned procedures, press <Ctrl-Y> to allocate a portion of the disk drives to the first logical drive. Then please follow the steps below.



1. Enter the desired capacity for the first logical drive and press <Enter>. The Define LD Menu displays again.




2. Press <Esc> to exit to the Main Menu. Press <Esc> again to exit the Utility.
3. Press <Y> to restart the computer.

You have successfully created a new RAID logical drive. Please install the operating system to your computer by following the detailed instruction of the "User Manual" in our support CD.


1.4.2 Configuring Legacy RAID ROM For AMD A88X/A78 Chipset

When the appropriate prompt appears during POST, press <Ctrl+R> to enter the RAID BIOS setup utility.




To create a new array, press <Enter> on the "Create Array" option.


*Be sure to delete the existing disk arrays before creating a new array.



Use the arrow keys to select the hard drives to be included in the RAID array and press <Ins>. The selected hard drives will be shown in green. To use all of the hard drives, simply press <A> to select all. Then press <Enter>.



Use the arrow keys to select a RAID level you want. Press <Enter> to confirm your selection.



Use the up/down arrow key or <PAGEUP> /<PAGEDOWN> to adjust the size and press <Enter>.

```

AMD-RAID Array Configuration (Build: 6.1.0-00118)
-----
Arrays                                     Disks
-----
                                     0-00,2.0TB,Ready
                                     1-01,2.0TB,Ready

Create Array
-----
Disks: 0,1
Type: RAID0
Total Size: 2.1TB

User Input
-----
Choose Size to Make Array

Size Chosen: 2TB Limit
DOS Size: 1.9TB
Exactly: 2,199,000,000,000

Available Keys
-----
<PAGEUP><↑><PAGEDOWN><↓>=Change Size
<Enter>=Complete, <Esc>=Go Back
  
```

Select a caching mode and press <Enter> to proceed.

```

AMD-RAID Array Configuration (Build: 6.1.0-00118)
Read and Write-back Caching. (Some data may be lost in a crash)
-----
Arrays                                     Disks
-----
                                     0-00,2.0TB,Ready
                                     1-01,2.0TB,Ready

Create Array
-----
Disks: 0,1
Type: RAID0
Total Size: 3.9TB

Caching Mode: Read/Write
User Input
-----
Select Caching Mode

Read/Write
Read Only
None

Available Keys
-----
<↑><↓><+><->=Choose, <Esc>=Back
<Enter>=Select Menu Item
  
```

Press <C> to confirm and then press <Esc> to return to the previous screen.

```

AMD-RAID Array Configuration (Build: 6.1.0-00118)
-----
Arrays                                     Disks
-----
                                     0-00,2.0TB,Ready
                                     1-01,2.0TB,Ready


Create Array
-----
Disks: 0,1
Type: RAID0
Total Size: 3.9TB

Caching Mode: Read/Write
User Input
-----

Confirm Creation of Array

Available Keys
-----
<C>=Confirm
<Esc>=Go Back, <M>=Main Menu
  
```

When completed, you will see the new array on the main screen. Press <Esc> to exit the RAID BIOS utility.



2. AMD Windows RAID Installation Guide

AMD Windows RAID Installation Guide is an instruction for you to configure RAID functions by using RAIDXpert RAID management software under Windows environment. The RAIDXpert software offers local and remote management and monitoring of all AMD SATA logical drives that exist anywhere on a network. Its browser-based GUI provides email notification of all major events/alarms, memory cache management, drive event logging, logical drive maintenance, rebuild, and access to all components in the RAID configuration (server, controller, logical drives, physical drives, and enclosure). RAIDXpert is designed to work with AMD SATA RAID controllers. Other brands of RAID controllers are not supported. Please read this guide carefully and follow the instructions below to configure and manage RAID functions.

2.1 Components of RAIDXpert Installation Software

RAIDXpert installation software will install two major components to your system:

1. RAIDXpert RAID management software: The RAIDXpert software installs on the PC with the AMD SATA RAID Controller (the "Host PC").
2. Java Runtime Environment (in a private folder): The RAIDXpert installation program installs a private JRE in folder _jvm under the same directory where RAIDXpert is installed. RAIDXpert uses this private JRE to avoid incompatibility issues with any other JREs that may be present on your system.

2.2 Browser Support


On the Host PC with the AMD Controller, where you install RAIDXpert, you must have one of the following browsers: Internet Explorer 6.0, Mozilla Suite 1.7, Mozilla Firefox 1.0, or Netscape Navigator 7.1.

If you do not have one of the above browsers, install the browser first and make it the default browser. Then install RAIDXpert. You must use one of the browsers listed above on your networked PC in order to access RAIDXpert over the network.


2.3 Installing RAIDXpert

Follow these steps to install RAIDXpert on your Windows-based PC or Server.

1. Boot the PC or server, launch Windows, and log in as the Administrator. If the computer is already running, exit all programs. If you are not logged in as the Administrator, log out, then log in again as the Administrator.
2. Insert the software CD into your CD-ROM drive.
3. Double-click the Install CD's icon to open it.
4. Double-click the Installer icon to launch it (right). The first RAIDXpert installation dialog box appears.
5. Follow the prompts in the installation dialog boxes.
6. When the first installation screen appears, choose an installer language from the dropdown menu.



7. When the Welcome screen appears, click the **Next** button.




8. When the License Agreement screen appears, click the "I accept the terms of the license agreement" option to proceed with installation. Then click the **Next** button to continue.

Note:


If you leave the "I do not accept the terms of the license" option selected, the installation will quit when you click **Next**.




9. When the Choose Install Folder screen appears, make your selection of a folder for the RAIDxpert applications you are installing. For example, the Windows default folder is: **C:\Program Files\AMD\RAIDxpert**
If you want a different folder, type its location or click the **Choose...** button and select a new location. Click the **Next** button when you are finished.




10. When the Check HTTP SSL screen appears, you can choose External Security. An explanation follows.
External SSL Security – Applies security to all connections involving the Internet or outside your company firewall. Security options are invisible to authorized users. AMD provides a default certificate for the server as well as for internal data communication. However, in some cases it is better to install and verify your own certificate for the webserver. And, if possible, verify your certificate by certificate authority like Verisign or Thwate. See your MIS Administrator for guidance. Click the **Next** button when you have made your choice.



11. When the Ready to Install screen appears, click the **Install** button to continue.



12. When the Install Complete screen appears, click the **Finish** button.



2.4 Logging into RAIDXpert

Choose RAIDXpert in the Windows Programs menu. Or, log on manually with your browser:

1. Launch the Browser.
2. In the Browser address field, type the entry explained below.

If you did *not* choose the External Security option during RAIDXpert installation, use the *Regular* connection.

If you chose the External Security option during RAIDXpert installation, use the *Secure* connection.

2.5 Regular Connection

RAIDXpert uses an HTTP connectionhttp://

- Enter the Host PC's IP address127.0.0.1 or localhost
- Enter the Port number:25902
- Add to launch RAIDXpert./amd

Together, your entry looks like this:

http://127.0.0.1:25902/ati or **http://localhost:25902/ati**

2.6 Secure Connection

RAIDXpert uses a secure HTTP connectionhttps://


- Enter the Host PC's IP address127.0.0.1 or localhost
- Enter the Port number:8443
- Add to launch RAIDXpert./amd

Together, your entry looks like this:

https://127.0.0.1:8443/amd or **https://localhost:8443/amd**

Note that the IP address shown above applies to a log-in at the Host PC. When you log in over a network, enter the Host PC's actual IP address or hostname.

Press the **Enter** key. Then, when the login screen appears, type **admin** in the Login ID field. Type **admin** again in the Password field. The RAIDXpert login and password are case sensitive.




Click the **Sign in** button. After sign-in, the RAIDXpert opening screen appears.



2.7 Creating a New Logical Drive


A logical drive is a collection of physical drives in a RAID. To create a new logical drive:

1. Click **Logical Drive View** in Tree View.
2. Click the **Create** tab in Management View. The Select RAID Level screen appears.
3. Select the option beside the RAID level you want for your logical drive. RAIDxpert displays the RAID levels you can use with the available physical drives.



4. In the Select Drive Type screen, click the following option:
 - **Free Drives** – Select all Free (unassigned) physical drives

The Select Drives screen appears.



5. Click the **Next** button.
6. If you want to split the capacity of your physical drives between two logical drives, enter the capacity for the first logical drive in the Logical Drive Size field. Or, to use the maximum capacity of the physical drives, check the Use Maximum Capacity box.

Logical Drive Size GB (☒ Use Maximum Capacity)

Please select at least 3 drives for RAID 5.

7. Click the physical drives to select them. Available drives have a black frame. Selected drives have a red frame.

Select Drives

RAID 5 Striped Parity: Data is striped over 3 or more drives, parity provides redundancy using less space. Best overall balance of performance, capacity and protection.

Logical Drive Size GB (☒ Use Maximum Capacity)

Please select at least 3 drives for RAID 5.

Drive on Port 1 - 81.9 GB	Free
Drive on Port 2 - 81.9 GB	Free
Drive on Port 3 - 81.9 GB	Free
Drive on Port 4 - 81.9 GB	Free
Drive on Port 5 - 81.9 GB	Free

☒ Selected
 ☐ Available
 ☐ Assigned
 ☐ Spare
 ☐ Invalid


8. Click the **Next** button. The Assign a Name screen appears.
9. Enter a name for the logical drive in the field provided.

Assign a Name

Assign a name to the logical drive.

Assigned Name (1-32 character(s))

10. Click the **Next** button. The Final Settings screen appears.
11. RAID 0, 5, and 10. Choose a Stripe Block Size from the dropdown menu. The choices are 64 and 128 KB. The Write Cache policy is None. You cannot change this setting.
12. RAID 0, 1, and 5. Select a Gigabyte Boundary policy from the dropdown menu.
 - **GigaByte Boundary** – Rounds the size of the logical drive down to the nearest whole gigabyte. This is the default. For more information.
 - **None** – No Boundary function.
13. Select an Initialization policy from the dropdown menu.
 - **Fast Initialization** – Erases the reserve and master boot sectors of the physical drives being added to the logical drive.
 - **Full Initialization** – Erases all sectors of the physical drives being added to the logical drive. RAID 0, 1 and 5 only.
 - **None** – No initialization. This choice is not recommended.



14. Click the **Finish** button. If there are physical drives available, the Select RAID Level screen appears again, where you can create an additional logical drive. Click the **Logical Drive** in Tree View to see all of the information about your new logical drive.



Before you can use your new logical drive, you must partition and format the logical drive using your PC's operating system.

2.8 Connecting to RAIDXpert from the Internet

The above instructions cover connections between the Host PC and other PCs using RAIDXpert over your company network. It is also possible to connect to a Host PC from the Internet.

Your MIS Administrator can tell you how to access your network from outside the firewall. Once you are logged onto the network, you can access the Host PC using its IP address.

Please note that only the Host PC can read and write data to the logical drives. However, other PCs can monitor the Host PC from virtually any location.

2.9 Running RAIDXpert without Network Connection

While RAIDXpert was designed to run over a network, you can run RAIDXpert without a network connection but only from the Host PC. Follow this procedure:

1. Choose RAIDXpert in the Windows Programs menu. Or choose RAIDXpert in the Linux Applications menu. Your


browser opens and displays a “no connection to the Internet is currently available” message.

2. Click the Work Offline button.
3. In the RAIDXpert login screen, enter your user name and password (if used), then click the Sign in button. A “webpage unavailable while offline” message will display.
4. Click the Connect button. A “no connection to the Internet is currently available” message will display.
5. Click the Try Again button.


After a few moments, RAIDXpert will display normally in your browser.

2.10 Using RAIDXpert2 to Create RAID Array in Windows (for AMD A88X/A78 Chipset)


1. When you install the all-in-one driver to your system from ASRock's support CD, AMD RAIDXpert2 will be auto-installed as well.




2. Execute RAIDXpert2 in the Windows Programs menu.




3. When the login screen appears, type “admin” in the Login ID field. Type “admin” again in the Password field.




4. Create new username and password. Then log in to RAIDXpert with new username & password.



- Be sure to delete the existing disk arrays before creating a new array.




- To create array, Click on Array → Create.




7. Select the disks to be included in the RAID array.

Select Array Type


Enter Array Name & Array Size. Then click **Create** to create a RAID array.



8. Check if the array is created successfully.



9. In Disk Management, create partition and initialize the disk as GPT.



Appendix –rcadm.efi information for AMD A88X/A78

rcadm -?

-?, --help

Displays all primary rcadm commands, or if used after an option, displays help for that specific option.

-log, --log-file

Print output to a log file as well as standard output. Requires a log file name argument. Overwrites existing file. Only one occurrence of this option on the command line is allowed.

Example: rcadm -M -qa -v -log status.txt

-C, --create

Command for creating arrays. Array types include linear (JBOD), volume (JBOD), RAID0, RAID1, RAID1n, RAID10, RAID10n, RAID5, RAID50, RAID6, RAID60, and RAIDable. Some of the major functions include assigning spare disks; setting array size; setting the number of disks in each submember of a RAID10n or RAID50 array; and setting cache attributes.

-D, --delete

Command for deleting arrays. This mode does not have any optional arguments.

-M, --manage

Commands for managing and querying controllers, arrays, and disks. Some of the major functions include querying for information, adding and removing dedicated and global spare disks, setting cache attributes for arrays and disks, performing consistency checks on redundant array types, initializing disks, prioritizing tasks for arrays, scanning arrays and disks for changes in status, and hiding or unhiding arrays.

rcadm -M

MANAGE

-a, --array

Used with certain options to specify arrays.

-as, --add-spare

Adds a dedicated spare disk to an array. No space is reserved on the disk selected.

-rs, --remove-spare

Removes a dedicated spare disk from an array.

- ras, --remove-all-spares
Removes any spares from an array.
- ags, --add-global-spare
Adds a disk as a global spare. No space is reserved on the disk selected.
- rgs, --remove-global-spare
Removes a global spare disk.
- ca, --cache-array
Sets the cache attributes for an array. Cache attributes include read cache (r), read and write-back cache (rw), write-back cache (w), and no cache (nc).
- cd, --cache-disk
Sets the cache attributes for a disk. Cache attributes include read cache (r), read and write-back cache (rw), write-back cache(w), and no cache (nc).
- d, --disk
A required qualifier used with certain options to specify disks.
- h, --hide
Hides an array from the operating system.
- uh, --unhide
Unhides an array, making it visible to the operating system.
- id, --initialize-disk
Initializes a disk. If the disk is new and has not been used, you must initialize it before you can create arrays.
- n, --name
Identifies an array with a user-supplied name. The name can be up to 30 characters, but only 17 of those characters display in the BIOS.
- p, --priority
Sets an array's task priority from 1-10, with 10 being the highest priority.
- q, --query
Lists information about specific controllers, arrays, and disks.
- qa, --query-all
Lists information about controllers, arrays, and disks.
- v, --verbose
Modifier of the --query and --query-all option. Specifies more detail for arrays and disks.
- rsc, --rescan
Rescans the serial ATA (SATA) channels for new or removed disks.
- sa, --scan-array <on|off>

- Specifies if background array scan scanning is on or off.
- sp, --smart-poll
Turns SMART polling on or off for the specified drive(s).
- t, --task
Used to pause, resume, and remove tasks.
- ul, --unlink
Unlinks two arrays linked through a create copy operation.

SYNTAX and EXAMPLES

ADD SPARE

--add-spare --array <list> --disk <list>

-as -a <list> -d <list>

Examples: rcadm --manage --add-spare --array * --disk 1

rcadm -M -as -a 1 2 -d 5 6

REMOVE SPARE

--remove-spare --array <list> --disk <list>

-rs -a <list> -d <list>

Examples: rcadm --manage --remove-spare --array 5 --disk *

rcadm -M -rs -a * -d 5

REMOVE ALL SPARES

--remove-all-spares --array <list>

-ras -a <list>

Examples: rcadm --manage --remove-all-spares --array 5

rcadm -M -ras -a *

ADD GLOBAL SPARE

--add-global-spare --disk <list>

-ags -d <list>

Examples: rcadm --manage --add-global-spare --disk 1 2 3

rcadm -M -ags -d *

REMOVE GLOBAL SPARE

--remove-global-spare --disk <list>

-rgs -d <list>

Examples: rcadm --manage --remove-global-spare --disk *

rcadm -M -rgs -d 5

CACHE SETTINGS FOR ARRAYS

--cache-array <cache_attribute> --array <list>

-ca <cache_attribute> -a <list>

Cache attributes: <r> for read cache

<rw> for read and write-back cache

<w> for write-back cache

<nc> for no cache

Examples: rcadm --manage --cache-array rw --array *

rcadm -M -ca nc -a 1

DISK SETTINGS (Advanced)

Disk cache:

--cache-disk <cache_attribute> --disk <list>

-cd <cache_attribute> -d <list>

Cache attributes: <r> for read cache

<rw> for read and write-back cache

<w> for write-back cache

<nc> for no cache

Examples: rcadm --manage --cache-disk r --disk 1 2 3

rcadm -M -cd w -d *

HIDE ARRAY

--hide --array <list>

-h -a <list>

Examples: rcadm --manage --hide --array 5 6

rcadm -M -h -a 4

UNHIDE ARRAY

--unhide --array <list>

-uh -a <list>

Examples: rcadm --manage --unhide --array *

rcadm -M -uh -a 5

INITIALIZE DISK

--initialize-disk --disk <list>

-id -d <list>

Examples: rcadm --manage --initialize-disk --disk *

rcadm -M -id -d 1 2 3

NAME ARRAY

--name "name" --array <list>

-n "name" -a <list>

Examples: rcadm --manage --name "System Disk" --array 5

rcadm -M -n "Backup Disk" -a 4

QUERY

--query [--array <list>] [--disk <list>]

[--verbose]

-q [-a <list>] [-ct <list>] [-d <list>] [-v]

Examples: rcadm --manage --query --array 1 --disk --verbose

rcadm -M -q -a 1 2 3 -d -v

QUERY ALL

--query-all

-qa

Example: rcadm --manage --query-all

RESCAN DISKS

--rescan

-rsc

Example: rcadm --manage --rescan

SCAN ARRAY

--scan-array <on|off> --array <array_number>

-sa <on|off> -a <array_number>

Example: rcadm -M --array 1 --scan-array on

rcadm -M -a 1 -sa off

SMART POLL

--smart-poll <on|off> --disk <list>

-sp <on|off> -d <list>

Example: rcadm --manage --smart-poll on --disk

rcadm -M -sp off -d 1 2 3

TASK CONTROL

--task <task_operation> --array <array_number>

-t <task_operation> -a <array_number>

Task Operation

<pause> to temporarily pause a task

<resume> to continue running a task

<remove> to permanently remove a task

Examples: rcadm --manage --task pause --array 5

rcadm -M -t remove -a 4

TASK PRIORITY

--priority <1..10> --array <list>

-p <1..10> -a <list>

Examples: rcadm --manage --priority 5 --array 6

rcadm -M -p 1 -a

UNLINK ARRAY

--unlink --array <array_number>

-ul -a <array_number>

Examples: rcadm --manage --unlink --array 2
rcadm -M -ul -a 5

rcadm -C

CREATE

Long form:

```
rcadm --create <raid_type> --disk <list> [--size <size_mb>]  
[--sub-member <num>] [--spare-disk <list>]  
[--no-sync] [--d-spare] [--cache <r,rw,w,nc>]  
[--max-size] [--name "name"] [--priority <1..10>]  
[--zero][--scan-array]
```

Short form:

```
rcadm -C <raid_type> -d <list> [-s <size_mb>] [-sub <num>]  
[-sp <list>] [-ns] [-ds] [-ca <r, rw, w, nc>] [-ms]  
[-n "name"] [-p <1..10>] [-z] [-sa] }
```

RAID Types:

--volume, -v Single disk or concatenation of disks

(JBOD)

--raidable, -ra	Single disk, RAIDable
--raid0, -r0	Stripe of two or more disks
--raid1, -r1	Mirror of two disks
--raid10, -r10	Stripe set of mirror sets
--raid5, -r5	Stripe set with parity, three to sixteen disks

OPTIONS

-sp, --spare-disk

Specifies the dedicated spare disk or disks to assign, with a maximum of four. No space is reserved on the selected disks.

-s, --size

Specifies the size of the array in MBs. If you do not use this option, the largest possible size is used by default.

-ns, --no-sync

Disables background synchronization of redundant types when creating the array.

-ca, --cache

Specifies a cache setting for the array(s): read cache <r>, read and write-back cache <rw>, write-back cache <w>, or no cache <nc>. The default is read and write-back cache <rw>.

-ms, --max-size

Prints the maximum possible size for an array without actually creating an array.

-n, --name

Identifies an array with a user-supplied name. The name can be up to 30 characters, but only 17 of those characters display in the BIOS.

-p, --priority

Sets the background initialization task priority from 1 to 10, with 10 being the highest priority. For redundant array types only.

-led, --leave-existing-data

Leaves the existing data on the disks untouched after the array is created. This option can be used to try to recover user data when an array has been accidentally deleted or the configuration information is lost but the data is still intact. Unless you immediately recreate the array after deleting it and no other tasks have been performed, the likelihood of recovering data with this method is very low.

-d, --disk

A required qualifier used with the --create option to specify the disk or disks to be included in the array.

-sa, --scan-array

Specifies that a background array scan should be continuously run whenever the array is idle (Default is off).

-z, --zero

Zero the array in the foreground. This method is faster than doing a background consistency verifies if the array is a redundant type. For non redundant types the zero option can be used to verify all blocks in the array can be accessed.

EXAMPLES

Example: Create a RAID5 set of the maximum possible size using all disks.

```
rcadm -C --raid5 --disk *
```

Example: Create a RAID1 set of the maximum possible size, with a spare disk and without a background initialization task.

```
rcadm -C --raid1 --spare-disk 3 --disk 1 2 --no-sync
```

Example: Print the maximum size a RAID5 array could be using all disks without actually creating the array.

```
rcadm -C --raid5 --disk * --max-size
```

rcadm -D

DELETE

Long form:

`--delete --array <list> [--no-ask]`

Short form:

`-D -a <list> [-na] [-cg <group number>]`

OPTIONS

`-na, --no-ask`

If the no ask option is specified the array is deleted without confirmation.

EXAMPLES

Example: Delete arrays 1 and 2.

`rcadm -D --array 1 2`

Example: Delete all arrays.

`rcadm -D --array`